

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 1 of 18

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

DRY-TREAT 40SK

SYNONYMS

"Water and salt protection", "Sandstone protection"

PROPER SHIPPING NAME

FLAMMABLE LIQUID, N.O.S.(contains acetone)

PRODUCT USE

Protection for masonry substrate.

SUPPLIER

Company: Dry- Treat Inc

Address:

1104 Philadelphia Pike

Willmington

DE, 19809

USA

Telephone: +1 866 667 5119

Telephone: +61 2 9954 3211

Emergency Tel: Outside USA +1 (813) 248 0585

Emergency Tel: CHEM- TEL (800) 255- 3924

Fax: +61 2 9954 3162

Company: Dry- Treat Ltd

Address:

3 North Street

Oatby

Leicester, LE2 5AH

GBR

Telephone: 0800 0964 760

Telephone: +61 2 9954 3211

Emergency Tel: Outside USA +1 (813) 248 0585

Emergency Tel: +61 2 9954 3211

Fax: +61 2 9954 3162

Company: Dry- Treat Pty Ltd

Address:

220 Pacific Highway

Crows Nest

NSW, 2065

AUS

Telephone: +61 2 9954 3211

Telephone: 1800 675 119

Emergency Tel: Outside USA +1 (813) 248 0585

Fax: +61 2 9954 3162

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.

POISONS SCHEDULE

None

RISK

- Highly flammable.
- Harmful by inhalation.
- Irritating to eyes respiratory system and skin.

SAFETY

- Keep away from sources of ignition. No smoking.
- Do not breathe gas/fumes/vapour/spray.
- Avoid contact with eyes.

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 2 of 18

Section 2 - HAZARDS IDENTIFICATION

- Harmful to aquatic organisms may cause long-term adverse effects in the aquatic environment.
- HARMFUL- May cause lung damage if swallowed.
- Repeated exposure may cause skin dryness and cracking.
- Vapours may cause drowsiness and dizziness.
- Wear suitable protective clothing.
- Use only in well ventilated areas.
- Keep container in a well ventilated place.
- Do not empty into drains.
- To clean the floor and all objects contaminated by this material use water and detergent.
- Keep container tightly closed.
- Keep away from food drink and animal feeding stuffs.
- In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.
- If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
- This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
ketone		<60
alkylalkoxysilane		<60
alkyl silicate		<60
dibutyltin dilaurate	77-58-7	<1
additives not contributing to the classification		balance

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

EYE

- If this product comes in contact with the eyes:
 - Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Seek medical attention without delay; if pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 3 of 18

Section 4 - FIRST AID MEASURES

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

■ Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

Treat symptomatically.

For acute or short term repeated exposures to acetone:

- Symptoms of acetone exposure approximate ethanol intoxication.
- About 20% is expired by the lungs and the rest is metabolised. Alveolar air half-life is about 4 hours following two hour inhalation at levels near the Exposure Standard; in overdose, saturable metabolism and limited clearance, prolong the elimination half-life to 25-30 hours.
- There are no known antidotes and treatment should involve the usual methods of decontamination followed by supportive care. [Ellenhorn and Barceloux: Medical Toxicology]

Management:

Measurement of serum and urine acetone concentrations may be useful to monitor the severity of ingestion or inhalation.

Inhalation Management:

- Maintain a clear airway, give humidified oxygen and ventilate if necessary.
- If respiratory irritation occurs, assess respiratory function and, if necessary, perform chest X-rays to check for chemical pneumonitis.
- Consider the use of steroids to reduce the inflammatory response.
- Treat pulmonary oedema with PEEP or CPAP ventilation.

Dermal Management:

- Remove any remaining contaminated clothing, place in double sealed, clear bags, label and store in secure area away from patients and staff.
- Irrigate with copious amounts of water.
- An emollient may be required.

Eye Management:

- Irrigate thoroughly with running water or saline for 15 minutes.
- Stain with fluorescein and refer to an ophthalmologist if there is any uptake of the stain.

Oral Management:

- No GASTRIC LAVAGE OR EMETIC
- Encourage oral fluids.

Systemic Management:

- Monitor blood glucose and arterial pH.
- Ventilate if respiratory depression occurs.
- If patient unconscious, monitor renal function.
- Symptomatic and supportive care.

The Chemical Incident Management Handbook:

Guy's and St. Thomas' Hospital Trust, 2000

BIOLOGICAL EXPOSURE INDEX

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 4 of 18

Section 4 - FIRST AID MEASURES

Determinant	Sampling Time	Index	Comments
Acetone in urine	End of shift	50 mg/L	NS

NS: Non-specific determinant; also observed after exposure to other material.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- Fight fire from a safe distance, with adequate cover.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control the fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
 - Severe fire hazard when exposed to heat, flame and/or oxidisers.
 - Vapour may travel a considerable distance to source of ignition.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Combustion products include: carbon dioxide (CO₂), silicon dioxide (SiO₂), other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

- 3YE

PERSONAL PROTECTION

Glasses:
Chemical goggles.

Gloves:
PVC chemical resistant type.

Respirator:
Type AX- P Filter of sufficient capacity

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet
Issue Date: 11-Feb-2010
NA317EC

CHEMWATCH 22-9860
Version No:2.0
CD 2010/1 Page 5 of 18

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

■ Chemical Class: ketones

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
LAND SPILL - SMALL				
cross- linked polymer - particulate	1	shovel	shovel	R, W, SS
cross- linked polymer - pillow	1	throw	pitchfork	R, DGC, RT
sorbent clay - particulate	2	shovel	shovel	R, I, P
wood fiber - pillow	3	throw	pitchfork	R, P, DGC, RT
treated wood fiber - pillow	3	throw	pitchfork	DGC, RT
foamed glass - pillow	4	throw	pitchfork	R, P, DGC, RT
LAND SPILL - MEDIUM				
cross- linked polymer - particulate	1	blower	skidloader	R, W, SS
cross- linked polymer - pillow	2	throw	skidloader	R, DGC, RT
sorbent clay - particulate	3	blower	skidloader	R, I, P
polypropylene - particulate	3	blower	skidloader	R, SS, DGC
expanded mineral - particulate	4	blower	skidloader	R, I, W, P, DGC
polypropylene - mat	4	throw	skidloader	DGC, RT

Legend

DGC: Not effective where ground cover is dense

R; Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT: Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988.

- Clear area of personnel and move upwind.

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 6 of 18

Section 6 - ACCIDENTAL RELEASE MEASURES

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse /absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights, heat or ignition sources.
- When handling, DO NOT eat, drink or smoke.
- Vapour may ignite on pumping or pouring due to static electricity.
- DO NOT use plastic buckets.
- Earth and secure metal containers when dispensing or pouring product.
- Use spark-free tools when handling.
- Avoid contact with incompatible materials.
- Keep containers securely sealed.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

- Glass container is suitable for laboratory quantities.
- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C)

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 7 of 18

Section 7 - HANDLING AND STORAGE

(i) : Removable head packaging;

(ii) : Cans with friction closures and

(iii) : low pressure tubes and cartridges may be used.

- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
- In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

STORAGE INCOMPATIBILITY

■ Ethyl silicate:

- reacts slowly with water forming ethanol
- reacts violently with strong oxidisers
- is incompatible with acids, nitrates
- attacks some plastics and rubber.

Acetone:

- may react violently with chloroform, activated charcoal, aliphatic amines, bromine, bromine trifluoride, chlorotriazine, chromic(IV) acid, chromic(VI) acid, chromium trioxide, chromyl chloride, hexachloromelamine, iodine heptafluoride, iodoform, liquid oxygen, nitrosyl chloride, nitrosyl perchlorate, nityl perchlorate, perchloromelamine, peroxomonosulfuric acid, platinum, potassium tert-butoxide, strong acids, sulfur dichloride, trichloromelamine, xenon tetrafluoride
- reacts violently with bromoform and chloroform in the presence of alkalis or in contact with alkaline surfaces.
- may form unstable and explosive peroxides in contact with strong oxidisers, fluorine, hydrogen peroxide (90%), sodium perchlorate, 2-methyl-1,3-butadiene
- can increase the explosive sensitivity of nitromethane on contact flow or agitation may generate electrostatic charges due to low conductivity
- dissolves or attacks most rubber, resins, and plastics (polyethylenes, polyester, vinyl ester, PVC, Neoprene, Viton).

Ketones in this group:

- are reactive with many acids and bases liberating heat and flammable gases (e.g., H₂).
- react with reducing agents such as hydrides, alkali metals, and nitrides to produce flammable gas (H₂) and heat.
- are incompatible with isocyanates, aldehydes, cyanides, peroxides, and anhydrides.
- react violently with aldehydes, HNO₃ (nitric acid), HNO₃ + H₂O₂ (mixture of nitric acid and hydrogen peroxide), and HClO₄ (perchloric acid).
- may react with hydrogen peroxide to form unstable peroxides; many are heat- and shock-sensitive explosives.

A significant property of most ketones is that the hydrogen atoms on the carbons next to the carbonyl group are relatively acidic when compared to hydrogen atoms in typical hydrocarbons. Under strongly basic conditions these hydrogen atoms may be abstracted to form an enolate anion. This property allows ketones, especially methyl ketones, to participate in condensation reactions with other ketones and aldehydes. This type of condensation reaction is favoured by high substrate concentrations and high pH (greater than 1 wt% NaOH).

- Avoid strong acids, bases.
- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry well ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 8 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA mg/m ³	STEL mg/m ³	Notes
Australia Exposure Standards	dibutyltin dilaurate (Tin, organic compounds (as Sn))	0.1	0.2	Sk

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
dibutyltin dilaurate	25	

MATERIAL DATA

DRY-TREAT 40SK:

- For ethyl silicate (syn: tetraethyl silicate)

OES TWA: 10 ppm, 87 mg/m³; STEL: 30 ppm, 260 mg/m³

Odour Threshold Value: 3.6 ppm (detection), 5 ppm (recognition)

Short exposures effect the eyes and nose as follows:

3000 ppm - extremely irritating and intolerable.

1500 ppm - lachrimatory and stinging

700 ppm - mild stinging

250 ppm - slightly irritating

Odour threshold: 5 ppm

Odour detection: 85 ppm

IDLH Level: 700 ppm

The TLV-TWA is thought to be protective against irritation to the eye and mucous membranes.

Odour Threshold Value: 3.6 ppm (detection), 699 ppm (recognition)

Saturation vapour concentration: 237000 ppm @ 20 C

NOTE: Detector tubes measuring in excess of 40 ppm, are available.

Exposure at or below the recommended TLV-TWA is thought to protect the worker against mild irritation associated with brief exposures and the bioaccumulation, chronic irritation of the respiratory tract and headaches associated with long-term acetone exposures. The NIOSH REL-TWA is substantially lower and has taken into account slight irritation experienced by volunteer subjects at 300 ppm. Mild irritation to acclimatised workers begins at about 750 ppm - unacclimatised subjects will experience irritation at about 350-500 ppm but acclimatisation can occur rapidly. Disagreement between the peak bodies is based largely on the view by ACGIH that widespread use of acetone, without evidence of significant adverse health effects at higher concentrations, allows acceptance of a higher limit.

Half-life of acetone in blood is 3 hours which means that no adjustment for shift-length has to be made with reference to the standard 8 hour/day, 40 hours per week because body clearance occurs within any shift with low potential for accumulation.

A STEL has been established to prevent excursions of acetone vapours that could cause depression of the central nervous system.

Odour Safety Factor(OSF)

OSF=38 (ACETONE).

DIBUTYLTIN DILAURATE:

■ Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

The no/lowest-observed-adverse-effect levels (NOAELs or LOAELs) in inhalation studies involving tri-n-butyltin chloride and bromide are 0.3-0.4 ppm (2-4 mg/m³) based on changes in the lungs, heart, liver, kidneys, nervous system and reproductive system in rodents. Oral administration of organotin compounds has induced toxicity in a number of differing organ systems, organs and lungs. The LOAEL for triethyltin bromide was 0.4 mg triethyltin/kg/day as 5 ppm in drinking water. The LOAELs for the most critical organ sites in

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 9 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

rats (i.e. the cellular immune response and CNS effects) are 0.15 and 0.23 mg/tin/kg body weight/day. Experience with ingested tri- and diethyltins in the treatment of staphylococcal infections, osteomyelitis, anthrax and acne suggests that humans react in a manner similar to rodents, but that the human is more sensitive to absorbed organic tin. The recommended TLV-TWA is thought to minimise the potential for adverse effects on immune function and the central nervous system. A STEL is also recommended to minimise acute symptoms such as eye and respiratory tract irritation, headaches and/or nausea. Based on an exposure to 0.1 mg/m³, a 70-kg worker breathing 10 m³ of air/8hr workday and assuming complete retention of the inhaled dose, would receive a daily exposure of 14.3 ug tin/kg body weight of an organotin compound. A skin notation was recommended based on animal data and the potential danger of enhanced absorption due to damaged skin present in many exposed workers.

Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
 - Wear safety footwear or safety gumboots, eg. Rubber.
- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
 - chemical resistance of glove material,
 - glove thickness and
 - dexterity
- Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
 - When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
 - Contaminated gloves should be replaced.
- Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 10 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	AX- AUS P	-
1000	50	-	AX- AUS P
5000	50	Airline *	-
5000	100	-	AX- 2 P
10000	100	-	AX- 3 P
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

■ For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Highly flammable liquid with a characteristic odour; partially miscible with water.

PHYSICAL PROPERTIES

State	LIQUID	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Not Available
Flash Point (°C)	- 17 (ketone)	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	0.84
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet
Issue Date: 11-Feb-2010
NA317EC

CHEMWATCH 22-9860
Version No:2.0
CD 2010/1 Page 11 of 18

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Swallowing of the liquid may cause aspiration of vomit into the lungs with the risk of haemorrhaging, pulmonary oedema, progressing to chemical pneumonitis; serious consequences may result. Signs and symptoms of chemical (aspiration) pneumonitis may include coughing, gasping, choking, burning of the mouth, difficult breathing, and bluish coloured skin (cyanosis). Accidental ingestion of the material may be damaging to the health of the individual. Ingestion of ethyl silicate may produce liver, kidney and lung damage. A single dose of undiluted hydrolysed ethyl silicate (syn: tetraethyl orthosilicate, hydrolysed) mg/kg body weight) given to 10 animals produced no deaths, nor toxicological symptoms; no abnormalities were seen during the test period nor at necroscopy.

EYE

■ Evidence exists, or practical experience predicts, that the material may cause severe eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Eye contact may cause significant inflammation with pain. Corneal injury may occur; permanent impairment of vision may result unless treatment is prompt and adequate. Repeated or prolonged exposure to irritants may cause inflammation characterised by a temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur. When 0.1 ml of the undiluted hydrolysed ethyl silicate (syn: tetraethyl orthosilicate, hydrolysed) was placed in the conjunctival sac for of the right eye of rabbits and rinsed after 24 hours, there was only slight irritation recorded within a seven day observation period. The vapour when concentrated has pronounced eye irritation effects and this gives some warning of high vapour concentrations. If eye irritation occurs seek to reduce exposure with available control measures, or evacuate area. The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, ulceration.

SKIN

■ The material produces moderate skin irritation; evidence exists, or practical experience predicts, that the material either

- produces moderate inflammation of the skin in a substantial number of individuals following direct contact, and/or
- produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.

Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

Skin contact with liquid ethyl silicate may result in dryness, cracking, inflammation.

Doses of >7940 mg/kg hydrolysed ethyl silicate (syn: tetraethyl orthosilicate) produced no systemic effects in rabbits. When applied for a single four hour exposure to the skin (semi-occluded), one rabbit of six showed slight erythema.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 12 of 18

Section 11 - TOXICOLOGICAL INFORMATION

INHALED

■ Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

Inhalation of ethyl silicate may cause nose irritation, unsteadiness, tremors, salivation, respiratory difficulty and unconsciousness. High concentrations can cause severe systemic injury including narcosis, liver and kidney damage and anaemia but at these concentrations the vapour becomes intolerable. Lung damage may also ensue.

Rats exposed to the vapour of hydrolysed ethyl silicate, (syn: tetraethyl orthosilicate, hydrolysed) for six hours (average vapour concentration 27100 mg/l) lived through the exposure and during a further 10 day observation period.

Inhalation hazard is increased at higher temperatures.

Systemic effects of acetone inhalation exposure include central nervous system depression, light-headedness, incoherent speech, ataxia, stupor, hypotension, tachycardia, metabolic acidosis, hyperglycaemia and ketosis. Rarely, convulsions and tubular necrosis may be evident. Other symptoms of exposure may include restlessness, headache, vomiting, low blood-pressure and rapid and irregular pulse, eye and throat irritation, weakness of the legs and dizziness. Inhalation of high concentrations may produce dryness of the mouth and throat, nausea, uncoordinated movement, loss of coordinated speech, drowsiness and, in severe cases, coma. Inhalation of acetone vapours over long periods causes irritation of the respiratory tract, coughing and headache. Rats exposed to 52200 ppm vapour for 1 hour showed clear signs of narcosis; fatalities occurred at 126600 ppm. Exposure to ketone vapours may produce nose, throat and mucous membrane irritation. High concentrations of vapour may produce central nervous system depression characterised by headache, vertigo, loss of coordination, narcosis and cardiorespiratory failure. Some ketones produce neurological disorders (polyneuropathy) characterised by bilateral symmetrical paresthesia and muscle weakness primarily in the legs and arms.

CHRONIC HEALTH EFFECTS

■ Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Workers exposed to 700 ppm acetone for 3 hours/day for 7-15 years showed inflammation of the respiratory tract, stomach and duodenum, attacks of giddiness and loss of strength. Exposure to acetone may enhance liver toxicity of chlorinated solvents.

TOXICITY AND IRRITATION

■ Not available. Refer to individual constituents.

DIBUTYLTIN DILAURATE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 175 mg/kg

IRRITATION

Skin (rabbit): 500 mg/24h - Mild

Eye (rabbit): 100 mg/24h - Moderate

SKIN

dibutyltin dilaurate

Australia Exposure Standards - Skin

Notes

Sk

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 13 of 18

Section 11 - TOXICOLOGICAL INFORMATION

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

DIBUTYLTIN DILAURATE:

DRY-TREAT 40SK:

■ DO NOT discharge into sewer or waterways.

■ Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DRY-TREAT 40SK:

Marine Pollutant: Not Determined

■ Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

■ Alkoxysilanes are highly toxic to algae and moderately toxic to aquatic invertebrates. e.g. the daphnid 48 hour LC50 for dimethyldiethoxysilane is 1.25 mg/l, and the 15-day algal EC50 for a number of alkoxysilanes is approximately 10 mg/l. Alkoxysilanes are used as coupling agents and are designed to hydrolyse.

Hydrolysis generally produces biodegradable alcohols.

Parameters controlling intrinsic stability and reactivity of organosilanols generated from alkoxysilanes in aqueous environments have been elucidated in several experiments. The studies indicate that the rates of hydrolysis of alkoxysilanes are generally related to their steric bulk, but demonstrate that after rate-limiting hydrolysis of the first alkoxy group steric effects are much less important.

■ For tetraethyl silicate:

Environmental fate;

Biodegradability:

98% DOC Die Away test; EC 79/831 Readily biodegradable.

Ecotoxicity:

Fish LC50 (96 h): *Brachydanio rerio* \geq 245 mg/l (acute toxicity test; EC 92/69)

Bacterial EC10 (5 h): *Pseudomonas putida* > 1878 mg/l (oxygen consumption test; on the lines of: Bringmann und Kuhn, Z. Wasser Abwasser Forsch. 10, 87-98 (1977))

Daphnia magna EC10 (48 h): > 844 mg/l (EC 84/449)

Algae EC50 (72 h): *Scenedesmus subspicatus* 410.4 mg/l (Cell multiplication inhibition test; EC 88/302).

■ For ketones:

Ketones, unless they are alpha, beta--unsaturated ketones, can be considered as narcosis or baseline toxicity compounds

Hydrolysis may also involve the addition of water to ketones to yield ketals under mild acid conditions.

However, this addition of water is thermodynamically favorable only for low molecular weight ketones. This addition is an equilibrium reaction that is reversible upon a change of water concentration and the reaction ultimately leads to no permanent change in the structure of the ketone substrate. The higher molecular weight ketones do not form stable ketals. Therefore, the ketones are stable to water under ambient environmental conditions

Another possible reaction of ketones in water involves the enolic hydrogen on the carbons bonded to the carbonyl function. Under conditions of high pH (pH greater than 10), the enolic proton is abstracted by base (OH-) forming a carbanion intermediate that may react with other organic substrates (e.g., ketones, esters, aldehydes) containing a center for nucleophilic attack. The reactions, commonly recognized as condensation reactions, produce higher molecular weight products. Under ambient conditions of temperature, pH, and low concentration, these condensation reactions are unfavorable.

Based on its reactions in air, it seems likely that ketones undergo photolysis in water. It is probable that ketones will be biodegraded to an appreciable degree by micro-organisms in soil and water. They are unlikely to bioconcentrate or biomagnify.

■ for acetone:

log Kow: -0.24

Half-life (hr) air: 312-1896

Half-life (hr) H2O surface water: 20

Henry's atm m³ /mol: 3.67E-05

BOD 5: 0.31-1.76, 46-55%

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 14 of 18

Section 12 - ECOLOGICAL INFORMATION

COD: 1.12-2.07

ThOD: 2.2

BCF: 0.69

Environmental fate:

Acetone preferentially locates in the air compartment when released to the environment. A substantial amount of acetone can also be found in water, which is consistent with the high water to air partition coefficient and its small, but detectable, presence in rain water, sea water, and lake water samples. Very little acetone is expected to reside in soil, biota, or suspended solids. This is entirely consistent with the physical and chemical properties of acetone and with measurements showing a low propensity for soil absorption and a high preference for moving through the soil and into the ground water

In air, acetone is lost by photolysis and reaction with photochemically produced hydroxyl radicals; the estimated half-life of these combined processes is about 22 days. The relatively long half-life allows acetone to be transported long distances from its emission source.

Acetone is highly soluble and slightly persistent in water, with a half-life of about 20 hours; it is minimally toxic to aquatic life.

Acetone released to soil volatilises although some may leach into the ground where it rapidly biodegrades.

Acetone does not concentrate in the food chain.

Acetone meets the OECD definition of readily biodegradable which requires that the biological oxygen demand (BOD) is at least 70% of the theoretical oxygen demand (THOD) within the 28-day test period

Drinking Water Standard: none available.

Soil Guidelines: none available.

Air Quality Standards: none available.

Ecotoxicity:

Testing shows that acetone exhibits a low order of toxicity

Fish LC50: brook trout 6070 mg/l; fathead minnow 15000 mg/l

Bird LC0 (5 day): Japanese quail, ring-neck pheasant 40,000 mg/l

Daphnia magna LC50 (48 h): 15800 mg/l; NOEC 8500 mg/l

Aquatic invertebrate 2100 - 16700 mg/l

Aquatic plant NOEC: 5400-7500 mg/l

Daphnia magna chronic NOEC 1660 mg/l

Acetone vapors were shown to be relatively toxic to two types insects and their eggs. The time to 50% lethality (LT50) was found to be 51.2 hr and 67.9 hr when the flour beetle (*Tribolium confusum*) and the flour moth (*Ephestia kuehniella*) were exposed to an airborne acetone concentration of 61.5 mg/m³. The LT50 values for the eggs were 30-50% lower than for the adult. The direct application of acetone liquid to the body of the insects or surface of the eggs did not, however, cause any mortality.

The ability of acetone to inhibit cell multiplication has been examined in a wide variety of microorganisms.

The results have generally indicated mild to minimal toxicity with NOECs greater than 1700 mg/L for exposures lasting from 6 hr to 4 days. Longer exposure periods of 7 to 8 days with bacteria produced mixed results; but overall the data indicate a low degree of toxicity for acetone. The only exception to these findings were the results obtained with the flagellated protozoa (*Entosiphon sulcatum*) which yielded a 3-day NOEC of 28 mg/L.

DIBUTYLTIN DILAURATE:

Marine Pollutant: Severe

- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Organotin compounds are characterized by a Sn⁴⁺ ion to which one to four organic ligands are attached. They are classified according to the type of organic ligand and the most common are butyltins, octyltins and phenyltins.

A large number of organotin substances are used in the society, and some of these are well-known environmental pollutants. The butyltins comprise on such group. Eco toxicity increases dramatically in the order methylbutyltin (MBT, R₃Sn) < dibutyltin (DBT, R₂Sn) < tributyltin (TBT, R₃Sn) for certain endpoints.

Degradation of organotin compounds involves the breaking of the tin-carbon bond, which may occur by UV irradiation, or by biological or chemical cleavage. In water, for example, tributyltin can be degraded by photochemical and biological processes relatively rapidly; however, adsorption onto suspended particulate material in water followed by sedimentation is a key removal process. The adsorption behavior of Sn⁴⁺ ion and eight organotin species (tri-, di-, and monobutyltin; tri-, di-, and monomethyltin; and tri- and diphenyltin) were studied in a water-sediment system using artificial seawater and estuarine sediment.

Adsorption coefficients varied from 100.5 to 104.5 and showed the trend of Sn⁴⁺ > mono > di > tri in the same substituent series. Larger absorption coefficients were found for aromatic compounds than for aliphatic

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 15 of 18

Section 12 - ECOLOGICAL INFORMATION

compounds. Releases of organotin compounds to air from various surfaces are, in general, not significant due to their low vapor pressures and rapid photodegradation at surfaces.

The speciation of organotin compounds is pH-dependent. At lower pHs, the cationic form will be the primary form, and as the pH is increased, the neutral hydroxide compounds will be the predominant species. In the environmentally relevant pH range (pH 5–9), the predominant organotin species will be the neutral hydroxide compounds (i.e., R_3SnOH , $R_2Sn(OH)_2$, and $RSn(OH)_3$). High concentrations of chloride favor the formation of chloro species. The pKa values for trimethyltin, triethyltin, tributyltin, and triphenyltin cations are approximately 6.60, 6.81, 6.25, and 5.2, respectively. Degradation of organotin compounds in sediments is much slower than in water, and half-lives have been estimated to be several years. In addition to dealkylation of organotin compounds, methylation of tin and organotin compounds by chemical and/or biological means may occur. The contribution of methylation by biotic and abiotic mechanisms is not clear. This pathway may result in fully substituted and volatile tin compounds.

At ambient temperatures, the solubilities of organotin compounds range from 0.0001 to about 50 mg/L. Organotin compounds may partition from water to aquatic organisms. The bioavailability of organotin compounds via the food chain appears to be of minor importance for tributyltin and triphenyltin when compared to uptake via the water phase. Seven-day BCF values were derived for dibutyltin dichloride, dibutyltin dilaurate, tributyltin chloride, bis(tributyltin) oxide, and triphenyltin chloride for muscle, liver, kidney, and vertebra tissue of round crucian carp. The BCF values ranged from 12 in muscle to 5,012 in liver. For all organotin compounds, liver had the highest BCF values. The highest BCFs were found for the tributyltin compounds.


The use of tributyltin (TBT) in antifouling paints on ships has caused significant harm to the marine environment worldwide. Female molluscs are masculinized by TBT at levels as low as ca 1 ng/l, and this effect has severe consequences for their ability to reproduce.

Most investigations on the environmental occurrence of organotin substances have focused on TBT. However, other substances such as dibutyltin (DBT), dioctyltin and monobutyltin (MBT) are used in the society for other reasons and are found in other applications.

Most industrial organotin chemicals (OTCs) are composed of an organotin cation and one or several ligands, and most of these chemicals are reconverted to the organotin cation compounds in natural waters. The cation may form dissolved complexes with e.g. chloride in seawater.

Therefore, their environmental partitioning properties such as K_d and K_h depend in part on the balancing anion in the environment. Hydrophobicity increases with increasing number of alkyl groups, and with increasing length of the alkyl chain. Organotins are moderately hydrophobic and associate strongly to particles in natural waters. In harbour sediments, log K_d in the range 3–4.3 have been measured for various OTCs, and the particle affinity increased in the order $MBT < DBT < TBT$. In various soils, however, the reverse pattern of K_d was observed. In organic soils, log K_d exceeded 4.0, whereas adsorption was less strong in mineral soils. In contrast to hydrophobic pollutants such as PCBs or PAHs (that partition to lipids in organic matter), OTCs are adsorbed to the functional groups of organic matter, e.g. phenolic and carboxylic groups.

Because organotins are generally cations, long-range atmospheric transport has generally not been considered as important. It has though been demonstrated that TBT forms highly volatile chloride species in seawater. One study has actually demonstrated the presence of organotins in air from rural sites, showing that long-range atmospheric transport of butyltins and octyltins do occur. MBT was the major species in precipitation and deposition. TBT mainly occurred in the gas phase and it is speculated that the source of butyltins may have been volatile TBT species. Subsequent dealkylation in the atmosphere may convert TBT to DBT and MBT. Organotins are progressively dealkylated in nature, for instance:



Dealkylation proceeds both by photolysis and through enzymatical reactions. This is important to consider when monitoring data are evaluated, since the occurrence of, e.g., DBT may be due to direct release of DBT or to release of TBT that is subsequently dealkylated. Half-lives in soils and sediments are commonly one or a few years, but may be longer under reducing conditions, whereas half-lives in natural waters may range from a few days to several weeks.

Organotin compounds have been detected in various marine organisms, from invertebrates to mammals. In fish and marine mammals, TBT and TPT bioaccumulate more strongly in liver than in muscle. Bioaccumulation is often stronger in bivalves than in fish, a consequence of lower metabolic capacity in bivalves. Trisubstituted OTCs are more strongly bioaccumulated than the less lipophilic disubstituted OTCs. Because TBT is dealkylated in many organisms, DBT may be a major species in biota but not necessarily the organotin species that was assimilated. Most studies do not suggest that TBT is biomagnified in aquatic food-chain. However, TPT appears to be biomagnified fairly strongly in the aquatic food chain. The trisubstituted substances, TPT and in particular TBT, are widely held as the most toxic organotin substances. Numerous field studies have

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 16 of 18

Section 12 - ECOLOGICAL INFORMATION

demonstrated a direct link between TBT and imposex in certain marine organisms, mainly molluscs. Imposex means that females are masculinized and this effect is severe because it directly influences the ability for organisms to reproduce. Imposex has been demonstrated in many coastal areas. These effects occur at very low levels (ca 1 ng/l) for certain organisms. It has been shown in laboratory that TBT causes masculinization also in fish. DBT and MBT does not cause imposex, but both TBT and DBT have negative effects on the reproductive system in mammals. In line with these facts, TBT and TPT were given the highest category in a European review of endocrine disrupting chemicals: "Evidence for endocrine disruption in living organisms". TBT was also classified as "Evidence of potential to cause endocrine disruption in humans".

Fish: LC50 (48 h): 58 mg/L

Bioaccumulation: not sig

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
dibutyltin dilaurate	HIGH		LOW	LOW

Section 13 - DISPOSAL CONSIDERATIONS

■ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 17 of 18

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:

●3YE (ADG7)

ADG7:

Class or division:	3	Subsidiary risk:	None
UN No.:	1993	UN packing group:	II
Special provisions:	274	Packing Instructions:	None
Notes:	None	Limited quantities:	1 L
Portable tanks and bulk containers - Instructions:	T7	Portable tanks and bulk containers - Special provisions:	TP1; TP8; TP28
Packagings and IBCs - Packing instruction:	P001; IBC02	Packagings and IBCs - Special packing provisions:	None

Shipping Name:FLAMMABLE LIQUID, N.O.S. (contains acetone)

Land Transport UNDG:

Class or division:	3	Subsidiary risk:	None
UN No.:	1993	UN packing group:	II

Shipping Name:FLAMMABLE LIQUID, N.O.S. (contains acetone)

Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	II
UN/ID Number:	1993	Packing Group:	II
Special provisions:	A3		

Shipping Name: FLAMMABLE LIQUID, N.O.S. *(CONTAINS ACETONE)

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1993	Packing Group:	II
EMS Number:	F- E, S- E	Special provisions:	274 330 944
Limited Quantities:	1 L	Marine Pollutant:	Not Determined

Shipping Name: FLAMMABLE LIQUID, N.O.S.(contains acetone)

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

None

REGULATIONS

Regulations for ingredients

dibutyltin dilaurate (CAS: 77-58-7) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

No data for Dry-Treat 40SK (CW: 22-9860)

Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

continued...

DRY-TREAT 40SK

Chemwatch Independent Material Safety Data Sheet

Issue Date: 11-Feb-2010

NA317EC

CHEMWATCH 22-9860

Version No:2.0

CD 2010/1 Page 18 of 18

Section 16 - OTHER INFORMATION

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 11-Feb-2010

Print Date: 11-Feb-2010

This is the end of the MSDS.