

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0
CD 2006/3 Page 1 of 15

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

DRY-TREAT 40SK

SYNONYMS

"masonry sealant", "stone consolidator"

PROPER SHIPPING NAME

FLAMMABLE LIQUID, N.O.S.

PRODUCT USE

Stone consolidator and water protection for masonry substrate.

SUPPLIER

Company: Dry- Treat Inc.

Address:

1201 Orange Street Suite 600

One Commerce Center

Willmington DE 19801

USA

Telephone: 1 866 667 5119

Telephone: +61 2 9954 3211

Emergency Tel: CHEM- TEL (800) 255- 3924 Outside

USA (813) 248- 0585

Emergency Tel: +61 2 9954 3211

Fax: +61 2 9954 3162

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

S5

RISK

Highly flammable.

Irritating to eyes, respiratory system and skin.

HARMFUL- May cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

SAFETY

Keep away from sources of ignition. No smoking.

Do not breathe gas/fumes/vapour/spray.

Avoid contact with eyes.

Wear suitable protective clothing.

Use only in well ventilated areas.

Keep container in a well ventilated place.

Do not empty into drains.

To clean the floor and all objects contaminated by this material, use water and detergent.

Keep container tightly closed.

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0

CD 2006/3 Page 2 of 15

Section 2 - HAZARDS IDENTIFICATION

Keep away from food, drink and animal feeding stuffs.

Take off immediately all contaminated clothing.

In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).

This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
acetone	67-64-1	30-60
alkylalkoxysilane		10-20
tetraethyl silicate	78-10-4	10-20
additives nonhazardous		1-10

Section 4 - FIRST AID MEASURES

SWALLOWED

If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0
CD 2006/3 Page 3 of 15
Section 4 - FIRST AID MEASURES

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Protheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For acute or short term repeated exposures to acetone:

- Symptoms of acetone exposure approximate ethanol intoxication.
- About 20% is expired by the lungs and the rest is metabolised. Alveolar air half-life is about 4 hours following two hour inhalation at levels near the Exposure Standard; in overdose, saturable metabolism and limited clearance, prolong the elimination half-life to 25-30 hours.
- There are no known antidotes and treatment should involve the usual methods of decontamination followed by supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

Management:

Measurement of serum and urine acetone concentrations may be useful to monitor the severity of ingestion or inhalation.

Inhalation Management:

- Maintain a clear airway, give humidified oxygen and ventilate if necessary.
- If respiratory irritation occurs, assess respiratory function and, if necessary, perform chest X-rays to check for chemical pneumonitis.
- Consider the use of steroids to reduce the inflammatory response.
- Treat pulmonary oedema with PEEP or CPAP ventilation.

Dermal Management:

- Remove any remaining contaminated clothing, place in double sealed, clear bags, label and store in secure area away from patients and staff.
- Irrigate with copious amounts of water.
- An emollient may be required.

Eye Management:

- Irrigate thoroughly with running water or saline for 15 minutes.
- Stain with fluorescein and refer to an ophthalmologist if there is any uptake of the stain.

Oral Management:

- No GASTRIC LAVAGE OR EMETIC
- Encourage oral fluids.

Systemic Management:

- Monitor blood glucose and arterial pH.
- Ventilate if respiratory depression occurs.
- If patient unconscious, monitor renal function.
- Symptomatic and supportive care.

The Chemical Incident Management Handbook:
Guy's and St. Thomas' Hospital Trust, 2000

BIOLOGICAL EXPOSURE INDEX

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0
CD 2006/3 Page 4 of 15
Section 4 - FIRST AID MEASURES

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant	Sampling Time	Index	Comments
Acetone in urine	End of shift	50 mg/L	NS

NS: Non-specific determinant; also observed after exposure to other material.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- Fight fire from a safe distance, with adequate cover.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control the fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
 - Severe fire hazard when exposed to heat, flame and/or oxidisers.
 - Vapour may travel a considerable distance to source of ignition.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Combustion products include: carbon dioxide (CO₂), silicon dioxide (SiO₂), other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM: 3[Y]E

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0
CD 2006/3 Page 5 of 15
Section 5 - FIRE FIGHTING MEASURES

Personal Protective Equipment

Breathing apparatus.
Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES


MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse /absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

PROTECTIVE ACTIONS FOR SPILL



From IERG (Canada/Australia)

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0

CD 2006/3 Page 6 of 15

Section 6 - ACCIDENTAL RELEASE MEASURES

Isolation Distance 25 metres
Downwind Protection Distance 300 metres
IERG Number 14

FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.
- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills".
LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.
- 5 Guide 128 is taken from the US DOT emergency response guide book.
- 6 IERG information is derived from CANUTEC - Transport Canada.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

acetone	8500 ppm
tetraethyl silicate	300 ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

acetone	8500 ppm
tetraethyl silicate	100 ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

acetone	1000 ppm
tetraethyl silicate	25 ppm

The threshold concentration below which most people will experience no appreciable risk of health effects:

acetone	1000 ppm
tetraethyl silicate	25 ppm

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0
CD 2006/3 Page 7 of 15
Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers. DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights, heat or ignition sources.
- When handling, DO NOT eat, drink or smoke.
- Vapour may ignite on pumping or pouring due to static electricity.
- DO NOT use plastic buckets.
- Earth and secure metal containers when dispensing or pouring product.
- Use spark-free tools when handling.
- Avoid contact with incompatible materials.
- Keep containers securely sealed.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

Packing as supplied by manufacturer. Plastic containers may only be used if approved for flammable liquid. Check that containers are clearly labelled and free from leaks.

- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C)
 - (i) : Removable head packaging;
 - (ii) : Cans with friction closures and
 - (iii) : low pressure tubes and cartridges may be used.
- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
- In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

STORAGE INCOMPATIBILITY

Acetone reacts violently with bromoform and chloroform in the presence of alkalis or in contact with alkaline surfaces.

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0
CD 2006/3 Page 8 of 15
Section 7 - HANDLING AND STORAGE

Avoid strong acids, bases.
Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry well ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC
Australia Exposure Standards	acetone (Acetone)	500	1185	1000	2375			
Australia Exposure Standards	tetraethyl silicate (Ethyl silicate)	10	85					

The following materials had no OELs on our record under the following CAS

- Dry-Treat 40SK (USA):

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
acetone		2, 500 [LEL]

NOTES

Values marked LEL indicate that the IDLH was based on 10% of the lower explosive limit for safety considerations even though the relevant toxicological data indicated that irreversible health effects or impairment of escape existed only at higher concentrations.

Not available. Refer to individual constituents.

INGREDIENT DATA

ACETONE:

Odour Threshold Value: 3.6 ppm (detection), 699 ppm (recognition)

Saturation vapour concentration: 237000 ppm @ 20 C

NOTE: Detector tubes measuring in excess of 40 ppm, are available.

Exposure at or below the recommended TLV-TWA is thought to protect the worker against mild irritation associated with brief exposures and the bioaccumulation, chronic irritation of the respiratory tract and headaches associated with long-term acetone exposures. The NIOSH REL-TWA is substantially lower and has taken into account slight irritation experienced by volunteer subjects at 300 ppm. Mild irritation to acclimatised workers begins at about 750 ppm - unacclimatised subjects

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0
CD 2006/3 Page 9 of 15

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

will experience irritation at about 350-500 ppm but acclimatisation can occur rapidly. Disagreement between the peak bodies is based largely on the view by ACGIH that widespread use of acetone, without evidence of significant adverse health effects at higher concentrations, allows acceptance of a higher limit.

Half-life of acetone in blood is 3 hours which means that no adjustment for shift-length has to be made with reference to the standard 8 hour/day, 40 hours per week because body clearance occurs within any shift with low potential for accumulation.

A STEL has been established to prevent excursions of acetone vapours that could cause depression of the central nervous system.

TETRAETHYL SILICATE:

Odour Threshold Value: 3.6 ppm (detection), 5 ppm (recognition)

Short exposures effect the eyes and nose as follows:

3000 ppm - extremely irritating and intolerable.

1500 ppm - lachrymatory and stinging

700 ppm - mild stinging

250 ppm - slightly irritating

85 ppm detectable by odour

The TLV-TWA is thought to be protective against irritation to the eye and mucous membranes.

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity,

are important in the selection of gloves.

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0
CD 2006/3 Page 10 of 15

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	AX- AUS	-
1000	50	-	AX- AUS
5000	50	Airline *	-
5000	100	-	AX- 2
10000	100	-	AX- 3
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Flammable liquid with a characteristic odour; partly mixes with water.

PHYSICAL PROPERTIES

Liquid.

Molecular Weight: Not Applicable

Melting Range (°C): Not Available

Solubility in water (g/L): Partly Miscible

pH (1% solution): Not Applicable

Volatile Component (%vol): Not Available

Relative Vapour Density (air=1): Not Available

Lower Explosive Limit (%): Not Available

Autoignition Temp (°C): Not Available

State: Liquid

Boiling Range (°C): Not Available

Specific Gravity (water= 1): Not Available

pH (as supplied): Not Applicable

Vapour Pressure (kPa): Not Available

Evaporation Rate: Not Available

Flash Point (°C): Not Available

Upper Explosive Limit (%): Not Available

Decomposition Temp (°C): Not Available

Viscosity: Not Available

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0
CD 2006/3 Page 11 of 15

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be damaging to the health of the individual. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733).

EYE

Evidence exists, or practical experience predicts, that the material may cause severe eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Eye contact may cause significant inflammation with pain. Corneal injury may occur; permanent impairment of vision may result unless treatment is prompt and adequate. Repeated or prolonged exposure to irritants may cause inflammation characterised by a temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0

CD 2006/3 Page 12 of 15

Section 11 - TOXICOLOGICAL INFORMATION

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo. Exposure to ketone vapours may produce nose, throat and mucous membrane irritation. High concentrations of vapour may produce central nervous system depression characterised by headache, vertigo, loss of coordination, narcosis and cardiorespiratory failure. Some ketones produce neurological disorders (polyneuropathy) characterised by bilateral symmetrical paresthesia and muscle weakness primarily in the legs and arms. Systemic effects of acetone inhalation exposure include central nervous system depression, light-headedness, incoherent speech, ataxia, stupor, hypotension, tachycardia, metabolic acidosis, hyperglycaemia and ketosis. Rarely, convulsions and tubular necrosis may be evident. Other symptoms of exposure may include restlessness, headache, vomiting, low blood-pressure and rapid and irregular pulse, eye and throat irritation, weakness of the legs and dizziness. Inhalation of high concentrations may produce dryness of the mouth and throat, nausea, uncoordinated movement, loss of coordinated speech, drowsiness and, in severe cases, coma. Inhalation of acetone vapours over long periods causes irritation of the respiratory tract, coughing and headache. Rats exposed to 52200 ppm vapour for 1 hour showed clear signs of narcosis; fatalities occurred at 126600 ppm.

CHRONIC HEALTH EFFECTS

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. Workers exposed to 700 ppm acetone for 3 hours/day for 7-15 years showed inflammation of the respiratory tract, stomach and duodenum, attacks of giddiness and loss of strength. Exposure to acetone may enhance liver toxicity of chlorinated solvents.

TOXICITY AND IRRITATION

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

ACETONE:

TOXICITY

Oral (man) TDL₀: 2857 mg/kg
Oral (rat) LD₅₀: 5800 mg/kg
Inhalation (human) TCL₀: 500 ppm
Inhalation (man) TCL₀: 12000 ppm/4 hr
Inhalation (man) TCL₀: 10 mg/m³/6 hr
Inhalation (rat) LC₅₀: 50100 mg/m³/8 hr
Dermal (rabbit) LD₅₀: 20000 mg/kg

IRRITATION

Eye (human): 500 ppm - Irritant
Eye (rabbit): 3.95 mg - SEVERE
Eye (rabbit): 20mg/24hr - Moderate
Skin (rabbit): 395mg (open) - Mild
Skin (rabbit): 500 mg/24hr - Mild

TETRAETHYL SILICATE:

TOXICITY

Oral (rat) LD₅₀: 6270 mg/kg
Inhalation (rat) LCL₀: 1000 ppm/4h
Dermal (rabbit) LD₅₀: 5878 mg/kg
Eye (rabbit): 500 mg/24h - Mild

IRRITATION

Skin (rabbit): 500mg/24h Moderate
Eye (human): 3000 ppm
Eye (rabbit): 100 mg Mild

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0
CD 2006/3 Page 13 of 15

Section 12 - ECOLOGICAL INFORMATION

Marine Pollutant:Not Determined

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

ACETONE:

Fish LC50 (96hr.) (mg/l):	8300- 40000
Daphnia magna EC50 (48hr.) (mg/l):	10
log Kow (Prager 1995):	- 0.24
log Kow (Sangster 1997):	- 0.24
log Pow (Verschueren 1983):	- 0.24
BOD5:	122%
ThOD:	72
Half- life Soil - High (hours):	168
Half- life Soil - Low (hours):	24
Half- life Air - High (hours):	2790
Half- life Air - Low (hours):	279
Half- life Surface water - High (hours):	168
Half- life Surface water - Low (hours):	24
Half- life Ground water - High (hours):	336
Half- life Ground water - Low (hours):	48
Aqueous biodegradation - Aerobic - High (hours):	168
Aqueous biodegradation - Aerobic - Low (hours):	24
Aqueous biodegradation - Anaerobic - High (hours):	672
Aqueous biodegradation - Anaerobic - Low (hours):	96
Aqueous biodegradation - Removal secondary treatment - High (hours):	75%
Aqueous biodegradation - Removal secondary treatment - Low (hours):	54%
Aqueous photolysis half- life - High (hours):	270
Photooxidation half- life water - High (hours):	3.97E+06
Photooxidation half- life water - Low (hours):	9.92E+04
Photooxidation half- life air - High (hours):	2790
Photooxidation half- life air - Low (hours):	279

DO NOT discharge into sewer or waterways.

log Kow: -0.24

Half-life (hr) air: 312-1896

Half-life (hr) H2O surface water: 20

Henry's atm m³ /mol: 3.67E-05

BOD 5 if unstated: 0.31-1.76,46-55%

COD: 1.12-2.07

ThOD: 2.2

BCF: 0.69

Toxicity Fish: LC50(96) 5540-13000mg/L

Toxicity invertebrate: cell mult. inhib. 28-7500mg/L

Bioaccumulation: not sig

Nitrif. inhib.: 75% decr. at 840mg/L

Anaerobic effects: sig degrad

Degradation Biological: sig

processes Abiotic: Rxn OH*,photodissoc

In air, acetone is lost by photolysis and reaction with photochemically produced hydroxyl radicals; the estimated half-life of these combined processes is about 22 days. The relatively long half-life allows acetone to be transported long distances from its emission source.

Acetone is highly soluble and slightly persistent in water, with a

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0
CD 2006/3 Page 14 of 15
Section 12 - ECOLOGICAL INFORMATION

half-life of about 20 hours; it is minimally toxic to aquatic life.
Acetone released to soil volatilises although some may leach into the ground where it rapidly biodegrades.
Acetone does not concentrate in the food chain.
Drinking Water Standard: none available.
Soil Guidelines: none available.
Air Quality Standards: none available.

TETRAETHYL SILICATE:

- Biodegradability:
98% DOC Die Away test; EC 79/831
Readily biodegradable.
- Toxicity to fish:
LC 50 (Brachydanio rerio): ≥ 245 mg/l 96 h fish,
acute toxicity test; EC 92/69
- Toxicity to bacteria:
EC 10 (pseudomonas putida): > 1878 mg/l 5 h,
oxygen consumption test; on the lines of:
Bringmann und Kuhn, Z. Wasser Abwasser Forsch.
10, 87-98 (1977)
- Toxicity to daphnia:
EC 10 Daphnia magna): > 844 mg/l 48 h EC 84/449
- Toxicity to algae:
EC 50 (Scenedesmus subspicatus): 410.4 mg/l 72 h
cell multiplication inhibition test; EC 88/302

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material)
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE LIQUID
HAZCHEM: 3[Y]E

UNDG:

Dangerous Goods Class:	3	Subrisk:	None
UN Number:	1993	Packing Group:	II
Shipping Name:	FLAMMABLE LIQUID, N.O.S.		

Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1993	Packing Group:	II
ERG Code:	3H		
Shipping Name:	Flammable liquid, n.o.s. *		

continued...

DRY-TREAT 40SK

Chemwatch Material Safety Data Sheet
Issue Date: 17-May-2006
NA317EC

CHEMWATCH 4671-34
Revision No:2.0
CD 2006/3 Page 15 of 15
Section 14 - TRANSPORTATION INFORMATION

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1993	Packing Group:	II
EMS Number:	F- E, S- E	Marine Pollutant:	Not Determined

Shipping Name: FLAMMABLE LIQUID, N.O.S.

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: S5

REGULATIONS

acetone (CAS: 67-64-1) is found on the following regulatory lists;
Australia - Australia New Zealand Food Standards Code - Processing Aids - Permitted extraction solvents
Australia Exposure Standards
Australia High Volume Industrial Chemical List (HVICL)
Australia Illicit Drug Reagents/Essential Chemicals - Category III
Australia Inventory of Chemical Substances (AICS)
Australia National Pollutant Inventory
Australia Poisons Schedule
IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances
OECD Representative List of High Production Volume (HPV) Chemicals
United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control - Table II (English)

tetraethyl silicate (CAS: 78-10-4) is found on the following regulatory lists;
Australia Exposure Standards
Australia Inventory of Chemical Substances (AICS)
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

EXPOSURE STANDARD FOR MIXTURES

4671-34

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 17-May-2006
Print Date: 20-Oct-2006