

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 1 of 16

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

PORCELAIN SEALER

SUPPLIER

Company: Dry- Treat Inc.

Address:

1201 Orange Street Suite 600

One Commerce Center

Willmington DE 19801

USA

Telephone: 1 866 667 5119

Telephone: +61 2 9954 3211

Emergency Tel: CHEM- TEL (800) 255- 3924 Outside

USA (813) 248- 0585

Company: Dry- Treat Ltd.

Address:

3 North Street Oatby

Leicester LE2 5AH

United Kingdom

Telephone: 0800 0964 760

Telephone: +61 2 9954 3211

Emergency Tel: Outside USA +1 (813) 248- 0585

Emergency Tel: +61 2 9954 3211

Fax: +61 2 9954 3162

Company: Dry- Treat Pty. Ltd.

Address:

220 Pacific Highway

Crows Nest, 2065

NSW

AUSTRALIA

Telephone: +61 2 9954 3211

Telephone: 1800 675 119

Emergency Tel: +61 2 9954 3211

Emergency Tel: Outside USA +1 (813) 248 0585

PRODUCT USE

Water and stain protection for masonry substrate.

SYNONYMS

"stain preventer", "masonry sealant"

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A DANGEROUS SUBSTANCE ACCORDING TO DIRECTIVE 1999/45/EC AND ITS AMENDMENTS.

RISK

Risk Codes

R11

R19

R36

R65

R67

Risk Phrases

Highly flammable.

May form explosive peroxides.

Irritating to eyes.

HARMFUL- May cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 2 of 16

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	INT HAZ	%
isopropanol	67-63-0	F,Xn	>60
EC NO: 200-661-7 R CODES: R11, R36, R67			
other ingredients not contributing to the classification			balance

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For acute or short term repeated exposures to isopropanol:

- Rapid onset respiratory depression and hypotension indicates serious ingestions that require careful cardiac and respiratory monitoring together with immediate intravenous access.

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 3 of 16

Section 4 - FIRST AID MEASURES

-
- Rapid absorption precludes the usefulness of emesis or lavage 2 hours post-ingestion. Activated charcoal and cathartics are not clinically useful. Ipecac is most useful when given 30 mins. post-ingestion.
 - There are no antidotes.
 - Management is supportive. Treat hypotension with fluids followed by vasopressors.
 - Watch closely, within the first few hours for respiratory depression; follow arterial blood gases and tidal volumes.
 - Ice water lavage and serial haemoglobin levels are indicated for those patients with evidence of gastrointestinal bleeding.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- Fight fire from a safe distance, with adequate cover.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control the fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
- Severe fire hazard when exposed to heat, flame and/or oxidisers.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include: carbon dioxide (CO₂), silicon dioxide (SiO₂), other pyrolysis products typical of burning organic material.

WARNING: Long standing in contact with air and light may result in the formation of potentially explosive peroxides.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:

Chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 4 of 16

Section 5 - FIRE FIGHTING MEASURES

Type AX Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

Chemical Class: alcohols and glycols

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
LAND SPILL - SMALL				
cross- linked polymer - particulate	1	shovel	shovel	R, W, SS
cross- linked polymer - pillow sorbent clay - particulate	1	throw	pitchfork	R, DGC, RT
wood fiber - pillow	2	shovel	shovel	R, I, P
treated wood fiber - pillow	3	throw	pitchfork	R, P, DGC, RT
foamed glass - pillow	3	throw	pitchfork	DGC, RT
	4	throw	pichfork	R, P, DGC, RT
LAND SPILL - MEDIUM				
cross- linked polymer - particulate	1	blower	skiloader	R, W, SS
polypropylene - particulate	2	blower	skiloader	W, SS, DGC
sorbent clay - particulate	2	blower	skiloader	R, I, W, P, DGC
polypropylene - mat	3	throw	skiloader	DGC, RT
expanded mineral - particulate	3	blower	skiloader	R, I, W, P, DGC
polyurethane - mat	4	throw	skiloader	DGC, RT

Legend

DGC: Not effective where ground cover is dense

R; Not reusable

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 6 of 16

Section 6 - ACCIDENTAL RELEASE MEASURES

box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills".

LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.

5 Guide 128 is taken from the US DOT emergency response guide book.

6 IERG information is derived from CANUTEC - Transport Canada.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

isopropanol 2000 ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

isopropanol 2000 ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

isopropanol 400 ppm

The threshold concentration below which most people will experience no appreciable risk of health effects:

isopropanol 400 ppm

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers. DO NOT allow clothing wet with material to stay in contact with skin.
- The substance accumulates peroxides which may become hazardous only if it evaporates or is distilled or otherwise treated to concentrate the peroxides. The substance may concentrate around the container opening for example.
- Purchases of peroxidisable chemicals should be restricted to ensure that the chemical is used completely before it can become peroxidised.
- A responsible person should maintain an inventory of peroxidisable chemicals or annotate the general chemical inventory to indicate which chemicals are subject to peroxidation. An expiration date should be determined. The chemical should either be treated to remove peroxides or disposed of before this date.
- The person or laboratory receiving the chemical should record a receipt date on the bottle. The individual opening the container should add an opening date.
- Unopened containers received from the supplier should be safe to store for 18 months.
- Opened containers should not be stored for more than 12 months.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 7 of 16

Section 7 - HANDLING AND STORAGE

- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights, heat or ignition sources.
- When handling, DO NOT eat, drink or smoke.
- Vapour may ignite on pumping or pouring due to static electricity.
- DO NOT use plastic buckets.
- Earth and secure metal containers when dispensing or pouring product.
- Use spark-free tools when handling.
- Avoid contact with incompatible materials.
- Keep containers securely sealed.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

DO NOT use aluminium or galvanised containers.

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C)
- (i) : Removable head packaging;
- (ii) : Cans with friction closures and
- (iii) : low pressure tubes and cartridges may be used.
- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
- In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

STORAGE INCOMPATIBILITY

Avoid storage with strong acids, acid chlorides, acid anhydrides, oxidising agents.

Secondary alcohols and some branched primary alcohols may produce potentially explosive peroxides after exposure to light and/ or heat.

Incompatible with aluminium. DO NOT heat above 49 deg. C. in aluminium equipment.

STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry well ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 8 of 16

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC
UK Workplace Exposure Limits (WELs)	isopropano l (Propan-2-ol)	400	999	1250	500			

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
isopropanol		2,000 [LEL]

NOTES

Values marked LEL indicate that the IDLH was based on 10% of the lower explosive limit for safety considerations even though the relevant toxicological data indicated that irreversible health effects or impairment of escape existed only at higher concentrations.

MATERIAL DATA

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

INGREDIENT DATA

ISOPROPANOL:

Odour Threshold Value: 3.3 ppm (detection), 7.6 ppm (recognition)
Exposure at or below the recommended TLV-TWA and STEL is thought to minimise the potential for inducing narcotic effects or significant irritation of the eyes or upper respiratory tract. It is believed, in the absence of hard evidence, that this limit also provides protection against the development of chronic health effects. The limit is intermediate to that set for ethanol, which is less toxic, and n-propyl alcohol, which is more toxic, than isopropanol.

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 9 of 16

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity,

are important in the selection of gloves.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	AX- AUS	-
1000	50	-	AX- AUS
5000	50	Airline *	-
5000	100	-	AX- 2
10000	100	-	AX- 3
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 10 of 16

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

-resistant.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Does not mix with water.

Floats on water.

Molecular Weight: Not Applicable

Melting Range (°C): Not Available

Solubility in water (g/L): Immiscible

pH (1% solution): Not Applicable

Volatile Component (%vol): Not Available

Relative Vapour Density (air=1): Not Available

Lower Explosive Limit (%): Not Available

Autoignition Temp (°C): Not Available

State: LIQUID

Boiling Range (°C): Not Available

Specific Gravity (water= 1): 0.80

pH (as supplied): Not Applicable

Vapour Pressure (kPa): Not Available

Evaporation Rate: Not Available

Flash Point (°C): 14

Upper Explosive Limit (%): Not Available

Decomposition Temp (°C): Not Available

Viscosity: Not Available

APPEARANCE

Highly flammable liquid with a characteristic odour; does not mix with water.

Liquid Viscosity: approx 1.5mm²/s Kinematics at 20°C

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733).

Accidental ingestion of the material may be damaging to the health of the individual.

Effects on the nervous system characterise over-exposure to higher aliphatic alcohols.

These include headache, muscle weakness, giddiness, ataxia, (loss of muscle coordination)

, confusion, delirium and coma. Gastrointestinal effects may include nausea, vomiting and

diarrhoea. In the absence of effective treatment, respiratory arrest is the most common

cause of death in animals acutely poisoned by the higher alcohols. Aspiration of liquid

alcohols produces an especially toxic response as they are able to penetrate deeply in

the lung where they are absorbed and may produce pulmonary injury. Those possessing lower

viscosity elicit a greater response. The result is a high blood level and prompt death at

doses otherwise tolerated by ingestion without aspiration. As a general observation,

alcohols are more powerful central nervous system depressants than their aliphatic

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 11 of 16

Section 11 - TOXICOLOGICAL INFORMATION

analogues. In sequence of decreasing depressant potential, tertiary alcohols with multiple substituent OH groups are more potent than secondary alcohols, which, in turn, are more potent than primary alcohols. The potential for overall systemic toxicity increases with molecular weight, principally because the water solubility is diminished and lipophilicity is increased.

EYE

Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.

Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

SKIN

The material may produce mild skin irritation; limited evidence or practical experience suggests, that the material either:

- produces mild inflammation of the skin in a substantial number of individuals following direct contact, and/or
- produces significant, but mild, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.

Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (non allergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Exposure to aliphatic alcohols with more than 3 carbons may produce central nervous system effects such as headache, dizziness, drowsiness, muscle weakness, delirium, CNS depression, coma, seizure, and neurobehavioural changes. Symptoms are more acute with higher alcohols. Respiratory tract involvement may produce irritation of the mucosa, respiratory insufficiency, respiratory depression secondary to CNS depression, pulmonary oedema, chemical pneumonitis and bronchitis. Cardiovascular involvement may result in arrhythmias and hypotension. Gastrointestinal effects may include nausea and vomiting. Kidney and liver damage may result following massive exposures. The alcohols are potential irritants being, generally, stronger irritants than similar organic structures that lack functional groups (e.g. alkanes) but are much less irritating than the corresponding amines, aldehydes or ketones. Alcohols and glycols (diols) rarely represent serious hazards in the workplace, because their vapour concentrations are usually less

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 12 of 16

Section 11 - TOXICOLOGICAL INFORMATION

than the levels which produce significant irritation which, in turn, produce significant central nervous system effects as well.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

CHRONIC HEALTH EFFECTS

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Porcelain Sealer (EUR)

TOXICITY AND IRRITATION

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

ISOPROPANOL:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (human) LDLo: 3570 mg/kg

Oral (human) TDLo: 223 mg/kg

Oral (man) TDLo: 14432 mg/kg

Oral (rat) LD50: 5045 mg/kg

Dermal (rabbit) LD50: 12800 mg/kg

IRRITATION

Skin (rabbit): 500 mg - Mild

Eye (rabbit): 10 mg - Moderate

Eye (rabbit): 100mg/24hr- Moderate

Eye (rabbit): 100 mg - SEVERE

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

MATERIAL	CARCINOGEN	MUTAGEN	REPROTOXIN	SENSITISER	SKIN
isopropanol	IARC:3				

CARCINOGEN

IARC: International Agency for Research on Cancer (IARC)

Carcinogens: isopropanol Category: 3

Section 12 - ECOLOGICAL INFORMATION

Marine Pollutant:Not Determined

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

ISOPROPANOL:

log Kow (Sangster 1997):

0.05

log Pow (Verschueren 1983):

- 0.5714285

BOD5:

60%

BOD20:

78%

COD:

2.23

ThOD:

2.4

Half- life Soil - High (hours):

168

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 13 of 16

Section 12 - ECOLOGICAL INFORMATION

Half- life Soil - Low (hours):	24
Half- life Air - High (hours):	72
Half- life Air - Low (hours):	6.2
Half- life Surface water - High (hours):	168
Half- life Surface water - Low (hours):	24
Half- life Ground water - High (hours):	336
Half- life Ground water - Low (hours):	48
Aqueous biodegradation - Aerobic - High (hours):	168
Aqueous biodegradation - Aerobic - Low (hours):	24
Aqueous biodegradation - Anaerobic - High (hours):	672
Aqueous biodegradation - Anaerobic - Low (hours):	96
Photooxidation half- life water - High (hours):	1.90E+05
Photooxidation half- life water - Low (hours):	4728
Photooxidation half- life air - High (hours):	72
Photooxidation half- life air - Low (hours):	6.2

DO NOT discharge into sewer or waterways.

log Kow: -0.16- 0.28

Half-life (hr) air: 33-84

Half-life (hr) H₂O surface water: 130

Henry's atm m³ /mol: 8.07E-06

BOD 5 if unstated: 1.19,60%

COD: 1.61-2.30,97%

ThOD: 2.4

Aquatic toxicity

(fish) 24-96h TLM: 42.5-240 mg/l

(fish) 96h LC50: 4200-9640 mg/l *

(daphnia) 48h EC50: 2285 mg/l *

BOD 20: >70% *

* [Akzo Nobel]

Section 13 - DISPOSAL CONSIDERATIONS

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction,
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

DO NOT allow wash water from cleaning or process equipment to enter drains.

It may be necessary to collect all wash water for treatment before disposal.

In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority.

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 14 of 16

Section 13 - DISPOSAL CONSIDERATIONS

cleaned and destroyed.

According to the European Waste Catalogue, Waste Codes are not product specific but application specific. Waste Codes should be assigned by the User based on the application in which the product is used.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID
HAZCHEM: 3[Y]E

Land transport ADR/RID (cross-border):

ADR/RID Class:	3	Hazard identification (Kemler):	33
UN Number:	1993	Packing Group:	II
Classification Code:	F1	Hazard Label:	3

Shipping name: FLAMMABLE LIQUID, N.O.S.
(contains isopropanol)

Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1993	Packing Group:	II
ERG Code:	3H		

Shipping Name: FLAMMABLE LIQUID, N.O.S. (contains isopropanol)

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1993	Packing Group:	II
EMS Number:	F- E, S- E	Marine Pollutant:	Not Determined

Shipping Name: FLAMMABLE LIQUID, N.O.S. (contains isopropanol)

Section 15 - REGULATORY INFORMATION

ANNEX 1

Ingredient	Annex 1 67/548/EEC
isopropanol	603-117-00-0

RISK

Risk Codes

R11

R19

R36

R65

R67

Risk Phrases

Highly flammable.

May form explosive peroxides.

Irritating to eyes.

HARMFUL- May cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 15 of 16

Section 15 - REGULATORY INFORMATION

SAFETY

Safety Codes	Safety Phrases
S16	Keep away from sources of ignition. No smoking.
S23	Do not breathe gas/fumes/vapour/spray.
S25	Avoid contact with eyes.
S36	Wear suitable protective clothing.
S51	Use only in well ventilated areas.
S09	Keep container in a well ventilated place.
S29	Do not empty into drains.
S401	To clean the floor and all objects contaminated by this material, use water and detergent.
S07	Keep container tightly closed.
S13	Keep away from food, drink and animal feeding stuffs.
S27	Take off immediately all contaminated clothing.
S26	In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
S46	If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
S60	This material and its container must be disposed of as hazardous waste.

ANNEX 2: Indications of Danger

F	Highly Flammable
Xn	Harmful

REGULATIONS

Porcelain Sealer (EUR) (CAS No: None):

No regulations applicable

isopropanol (CAS: 67-63-0) is found on the following regulatory lists:

EU Directive 2002/72/EC Plastic materials and articles intended to come into contact with foodstuffs - Annex II Section A: List of authorised monomers and other starting substances

EU Directive 2002/72/EC Plastic materials and articles intended to come into contact with foodstuffs - Annex III Section A Incomplete list of additives fully harmonised at Community level

European Customs Inventory of Chemical Substances (English)

European Inventory of Existing Commercial Substances - EINECS

European Union (EU) Control of Major Accident Hazards Involving Dangerous Substances - Seveso Category

European Union (EU) Inventory of Fragrance Ingredients (Perfume and Aromatic Raw Materials)

European Union (EU) Inventory of Ingredients used in Cosmetic Products

European Union (EU) List of Dangerous Substances (Annex I) - up to the 29th ATP

European Union (EU) Restrictions on the Marketing and Use of Certain Dangerous Substances and Preparations

IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances

International Agency for Research on Cancer (IARC) Carcinogens

OECD Representative List of High Production Volume (HPV) Chemicals

UK Workplace Exposure Limits (WELs)

This safety data sheet is in compliance with the following

EU legislation and its adaptations – as far as applicable - : 67/548/EEC, 1999/45/EC, 76/769/EEC, 98/24/EC, 92/85/EEC, 94/33/EC, 91/689/EEC, 1999/13/EC,

as well as the following British legislation:

- The Control of Substances Hazardous to Health Regulations (COSHH) 2002
- COSHH Essentials
- The Management of Health and Safety at Work Regulations 1999

Section 16 - OTHER INFORMATION

RISK

continued...

PORCELAIN SEALER

Chemwatch Material Safety Data Sheet (Conforms to Regulation (EC) No 1907/2006)

Issue Date: 25-Jul-2007

NA160EC

CHEMWATCH 6619-24

Version No:2

CD 2007/2 Page 16 of 16

Section 16 - OTHER INFORMATION

Explanation of Risk Codes used in the Ingredient Table

Risk Codes

R11

R36

R67

Risk Phrases

Highly flammable.

Irritating to eyes.

Vapours may cause drowsiness and dizziness.

ANNEX 2: Indications of Danger

F

Highly Flammable

Xi

Irritant

Issue Date: 25-Jul-2007

Print Date: 25-Jul-2007

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.